



GROOVED COUPLINGS



XGQT1
Rigid Coupling

Nominal Size		Pipe O.D.	Max. Working Pressure		Max End Load	Bolt Size	Dimensions		
Inch	mm	mm	KPa	psi	N	mm	Φ	L	H
1	25	33.7	2065	300	2230	2-M10x55	58.5	94	47
1 1/4	32	42.4	2065	300	3530	2-M10x55	67.5	104	47
1 1/2	40	48.3	2065	300	4581	2-M10x55	74.5	111	47
2	50	57	2065	300	6379	2-M10x65	86	119	47
2	50	60.3	2065	300	7139	2-M10x65	88	121	47
2 1/2	65	73	2065	300	10463	2-M10x65	96.5	134	47
2 1/2	65	76.1	2065	300	11371	2-M10x65	104	136	47
3	80	88.9	2065	300	15518	2-M10x65	116	150	47
4	100	108	2065	300	22902	2-M10x65	140	176	51
4	100	114.3	2065	300	25652	2-M10x65	148	185	51
5	125	133	2065	300	34732	2-M12x85	168	210	51
5	125	139.7	2065	300	38319	2-M12x85	173	216	51
5	125	141.3	2065	300	39202	2-M12x85	175	219	51
6	150	159	2065	300	49639	2-M12x85	192	236	51
6	150	165.1	2065	300	53521	2-M12x85	200	244	51
6	150	168.3	2065	300	55616	2-M12x85	204	248	51
8	200	216.3	2065	300	91863	2-M16x120	257	316	63
8	200	219.1	2065	300	94257	2-M16x120	258	332	63
10	250	267.4	1205	175	89853	2-M20x130	309	387	63
10	250	273	1205	175	93656	2-M20x130	318	395	63
12	300	318.5	1205	175	127476	2-M20x130	361	434	63
12	300	323.9	1205	175	131835	2-M20x130	372	445	63